

CLIPPEDIMAGE= JP411236553A  
PAT-NO: JP411236553A  
DOCUMENT-IDENTIFIER: JP 11236553 A  
TITLE: WATER STOP SEAL MATERIAL

PUBN-DATE: August 31, 1999

INVENTOR-INFORMATION:

NAME	COUNTRY
TACHIBANA, KATSUHIKO	N/A
MATSUNAGA, MANABU	N/A

ASSIGNEE-INFORMATION:

NAME	COUNTRY
NITTO DENKO CORP	N/A

APPL-NO: JP10041828  
APPL-DATE: February 24, 1998

INT-CL (IPC): C09K003/10; B32B005/18 ; B32B007/10 ; B32B027/00 ;  
B32B027/36  
; C09J007/02 ; C09J169/00

ABSTRACT:

PROBLEM TO BE SOLVED: To obtain a water stop seal material having excellent sealability by forming a layer comprising a pressure-sensitive adhesive composition containing a polymer having a specified polycarbonate structure on at least either surface of a foam structure through a base material.

SOLUTION: A foam structure having closed cells or both closed cells and open cells is used, and a pressure-sensitive adhesive composition containing a polymer having repeating units of the formula (R is a 2-20C hydrocarbon group) is used. The molecular weight of the polymer is suitably 10,000 or above in terms of a weight-average molecular weight. The polymer used is a polyester synthesized from a polycarbonate diol and a dicarboxylic acid, a polyester synthesized from a polycarbonate dicarboxylic acid and a diol, or a polyurethane synthesized from a polycarbonate diol and a

diisocyanate, and is particularly desirably a polyester synthesized from a polycarbonate diol and a dicarboxylic acid. The water stop seal material is prepared by forming a pressure-sensitive adhesive composition layer having a thickness of, usually, 2-100

COPYRIGHT: (C) 1999, JPO